

M50 ACD

INDUSTRIAL VACUUM CLEANERS



- ✓ Simultaneous vacuuming of dust, liquids and solids.
- ✓ ACD classification for vacuuming combustible dust in non-classified zones

Suction unit

Usage area		Ordinary location
EX category		CE ACD
Power	kW	4
Max waterlift	mmH2O	2.600
Max air flow	m3/h	420
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	74

Filtering Unit

Primary filter		Star
Surface - Diameter	cm ² -mm	20.000 - 420
Total filtering surface area	cm ²	26.000
Material - Efficiency	IEC 60335-2-69	M ANT

Collection unit

Capacity	lt	100
----------	----	-----

Encumbrances

Dimensions	cm	119x65x160h
Weight	kg	138

APPLICATIONS:



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

M50 ACD

INDUSTRIAL VACUUM CLEANERS

FILTERING UNIT

The filter can be cleaned by means of the integrated mechanical cleaning system: an external filter shaking lever shakes the filter with a vertical movement, ensuring an effective and safe cleaning action, maintaining constant suction power and preventing the dispersion of dust into the environment.

COLLECTION UNIT

The vacuumed material is collected in a stainless steel detachable container, mounted on wheels, which allows for quick and clean disposal. Bagging is also possible.

OPTIONALS

- ✔ Star-delta starter panel board