

# MHD 130-180-250 HV

INDUSTRIAL VACUUM CLEANERS



- ✓ Extremely silent.
- ✓ Integrated filter cleaning system
- ✓ Large capacity detachable container. Forklift intakes.

## Suction unit

Voltage	V - Hz	400 - 50 3~
Power	kW	11 17,3 20
Max waterlift	mmH2O	5.100 - 6.000 - 5.000
Continuous water lift	mmH2O	4.300 - 5.400 - 4.400
Max air flow	m3/h	520 - 720 - 1.100
Suction inlet	mm	120
Noise level (EN ISO 3744)	dB(A)	78

## Filtering Unit

Primary filter		Star
Surface - Diameter	cm <sup>2</sup> -mm	70.000 - 560
Material - Efficiency	IEC 60335-2-69	Polyester L

## Collection unit

Capacity	lt	160
----------	----	-----

## Encumbrances

Dimensions	cm	163x76x200h
Weight	kg	390 - 421 - 450

## APPLICATIONS:



All data mentioned in this document may change without notice.  
Tutti i dati in questo documento potrebbero variare senza preavviso.

[www.dupuyvacuums.com](http://www.dupuyvacuums.com)  
[info@dupuy.it](mailto:info@dupuy.it)

# MHD 130-180-250 HV

INDUSTRIAL VACUUM CLEANERS

## **FILTERING UNIT**

---

The polyester pocket filter is located inside the steel filtering chamber and protects the suction unit, ensuring high dust retention and purity of the exhaust air thanks to its large surface area and high filtration efficiency. A manual cleaning system, consisting of a vertically moving filter shaker, allows the operator to clean the filter effortlessly at any time, extending the filter's life and preventing it from becoming saturated and reducing suction power. The suction system positioned below the filter allows the simultaneous suction of dust, solids and liquids without the need to replace or remove the filter.

## **COLLECTION UNIT**

---

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.