



- ✓ Maintenance-free motor suitable for continuous operation.
- ✓ Extremely silent.
- ✓ Large capacity detachable container. Forklift intakes.

### Suction unit

Voltage	V - Hz	400 - 50 3~
Power	kW	7,5 - 11 - 12,5 - 18,5
Max waterlift	mmH2O	4.500 - 4.000 - 4.400 - 4.400
Continuous water lift	mmH2O	3.200 - 2.600 - 2.900 - 3.200
Max air flow	m3/h	750 - 1.050 - 1.100 - 1.350
Suction inlet	mm	120
Noise level (EN ISO 3744)	dB(A)	74 - 75 - 78 - 81

### Filtering Unit

Primary filter		Star
Surface - Diameter	cm <sup>2</sup> -mm	70.000 - 560
Material - Efficiency	IEC 60335-2-69	Polyester L

### Collection unit

Capacity	lt	160
----------	----	-----

### Encumbrances

Dimensions	cm	163x76x200h
Weight	kg	332 - 390 - 430 - 430

### APPLICATIONS:

## **FILTERING UNIT**

The polyester filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

## **COLLECTION UNIT**

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.