

SILOVAC 100 HV AD

CENTRAL VACUUM SYSTEMS – CENTRAL VACUUM UNITS AND FILTER SILOS



- ✓ Balanced flap discharge system
- ✓ Easy and quick big-bag bagging.
- ✓ Large capacity detachable container. Forklift intakes.

Suction unit

Voltage	V - Hz	230 - 50 1~
Power	kW	2 x 1,6
Max waterlift	mmH2O	3600
Max air flow	m3/h	340
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	78

Filtering Unit

Surface - Diameter	cm ² -mm	20.000 - 420
--------------------	---------------------	--------------

Collection unit

Capacity	lt	100
----------	----	-----

Encumbrances

Dimensions	cm	139x126x294h
Weight	kg	160

APPLICATIONS:



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

SILOVAC 100 HV AD

CENTRAL VACUUM SYSTEMS – CENTRAL VACUUM UNITS AND FILTER SILOS

FILTERING UNIT

The filter can be cleaned by means of the integrated mechanical cleaning system: an external filter shaking lever shakes the filter with a vertical movement, ensuring an effective and safe cleaning action, maintaining constant suction power and preventing the dispersion of dust into the environment.

COLLECTION UNIT

The material is unloaded directly into big-bags.