

Fumebuster AC – Activated carbon welding fume extractor

AIR FILTRATION SOLUTIONS



- ✓ Accessories included, ideal for cleaning professionals.
- ✓ Compressed air supply via 2 Venturi units

Suction unit

| | | |
|---------------------------|--------|-------------|
| Voltage | V - Hz | 400 - 50 3~ |
| Power | kW | 1,5 |
| Max air flow | m3/h | 1300 |
| Suction inlet | mm | 150 |
| Noise level (EN ISO 3744) | dB(A) | 72 |

Filtering Unit

| | |
|-----------------------|--------|
| Cleaning system | Manual |
| Filtration efficiency | F9 95% |

Collection unit

| | | |
|------------------|----------------|-----|
| Capacity | lt | 200 |
| Liquid capacity | lt | 50 |
| Collection tank | Painted | |
| Cyclon unit | Integrated | |
| Discharge system | Disposable bag | |

Encumbrances

| | | |
|------------|----|----------------|
| Dimensions | cm | 65 x 75 x 129h |
| Weight | kg | 131 |

APPLICATIONS:



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

Fumbuster AC – Activated carbon welding fume extractor

AIR FILTRATION SOLUTIONS

SUCTION UNIT

It is equipped with an electric fan that provides a high airflow, ideal for direct extraction of volatile chips generated by machine tool processes or suspended dust present in work environments.

FILTERING UNIT

The vacuum cleaner is equipped with a progressive filtration consisting of panel filters with 4 stages of filtration.

COLLECTION UNIT

Container made entirely of AISI 316 stainless steel

OPTIONALS

- ✓ Local remote start-up
- ✓ Local/remote control
- ✓ Stainless steel chamber