

Fumevac, welding fume extractor

AIR FILTRATION SOLUTIONS



- ✓ Compact and portable industrial vacuum cleaner.
- ✓ Possibility of localised vacuuming thanks to an optional extraction arm
- ✓ Quick and easy filter replacement system.

Suction unit

Voltage	V - Hz	230 - 50 1~
Power	kW	1,1
Max waterlift	mmH2O	2.400
Max air flow	m3/h	180
Suction inlet	mm	50
Construction		Painted steel
Noise level (EN ISO 3744)	dB(A)	74

Filtering Unit

Primary filter		Cartridge
Surface - Diameter	cm ² -mm	7.500 - 245
Material - Efficiency	IEC 60335-2-69	Poliestere M
Filtration efficiency		H14 - 99,995%

Collection unit

Powder capacity	lt	13
Collection system		Release container

Encumbrances

Dimensions	cm	40 x 56 x 86h
Weight	kg	25

APPLICATIONS:



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

Fumevac, welding fume extractor

AIR FILTRATION SOLUTIONS

SUCTION UNIT

The suction is developed by one or two carbon brush by-pass motors, operated by independent switches and placed in a solid metal head, soundproofed with sound-absorbing material.

FILTERING UNIT

The filter can be cleaned by means of the integrated 'Dustop' reverse air cleaning system: by closing the suction nozzle and opening the flap on the filter chamber, the air flow from the motors is directed through the filter, effectively and safely cleaning it and preventing the dispersion of dust into the environment.

COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

OPTIONALS

- ✓ Hepa absolute filter /h14
- ✓ Activated carbon filter