

PROVAC 150 D

INDUSTRIAL VACUUM CLEANERS



- ✓ Accessories included, ideal for cleaning professionals.
- ✓ Extremely silent.
- ✓ Compact and portable industrial vacuum cleaner.

Suction unit

| | | |
|---------------------------|--------|-------------|
| Voltage | V - Hz | 230 - 50 1~ |
| Power | kW | 0,9 |
| Max waterlift | mmH2O | 1.900 |
| Max air flow | m3/h | 180 |
| Noise level (EN ISO 3744) | dB(A) | 64 |

Filtering Unit

| | | |
|------------------------------|-----------------|-------------|
| Primary filter | | Bag |
| Total filtering surface area | cm ² | 1.000 |
| Material - Efficiency | IEC 60335-2-69 | Polyester L |
| Cleaning system | | Manual |

Collection unit

| | | |
|-----------------|----|----|
| Powder capacity | lt | 15 |
|-----------------|----|----|

Encumbrances

| | | |
|------------|----|-----------|
| Dimensions | cm | 38x34x44h |
| Weight | kg | 8 |

APPLICATIONS:  General housekeeping



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

PROVAC 150 D

INDUSTRIAL VACUUM CLEANERS

SUCTION UNIT

Suction is generated by one carbon brush by-pass motor activated by independent switches located on a solid metal head that protects the motor from possible blows and ingress of external bodies, keeping the noise level to a minimum.

FILTERING UNIT

The polyester bag filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.