

PROVAC 300 WD

INDUSTRIAL VACUUM CLEANERS



- ✓ Accessories included, ideal for cleaning professionals.
- ✓ A powerful by-pass motor with independent cooling
- ✓ Extremely silent.
- ✓ Compact and portable industrial vacuum cleaner.

Suction unit

| | | |
|---------------------------|--------|-------------|
| Voltage | V - Hz | 230 - 50 1~ |
| Power | kW | 1,1 |
| Max waterlift | mmH2O | 2.400 |
| Max air flow | m3/h | 180 |
| Noise level (EN ISO 3744) | dB(A) | 67 |

Filtering Unit

| | | |
|------------------------------|-----------------|-------------|
| Primary filter | | Bag |
| Total filtering surface area | cm ² | 2.000 |
| Material - Efficiency | IEC 60335-2-69 | Polyester L |
| Cleaning system | | Manual |

Collection unit

| | | |
|----------|----|----|
| Capacity | lt | 34 |
|----------|----|----|

Encumbrances

| | | |
|------------|----|-----------|
| Dimensions | cm | 37x39x68h |
| Weight | kg | 12 |

APPLICATIONS:  General housekeeping

 **DUPUY**

All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

PROVAC 300 WD

INDUSTRIAL VACUUM CLEANERS

SUCTION UNIT

Suction is generated by one carbon brush by-pass motor activated by independent switches located on a solid metal head that protects the motor from possible blows and ingress of external bodies, keeping the noise level to a minimum.

FILTERING UNIT

The polyester bag filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The vacuum cleaner consists of a stainless steel drum with impact protection around the container equipped with swivelling wheels. It is possible to bag the dust directly in black waste bags.