

Fixed suction units

INDUSTRIAL VACUUM CLEANERS



- ✓ Maintenance-free motor suitable for continuous operation.

Suction unit

Voltage	V - Hz	400 - 50 ~ 3
Power	kW	0,85 - 4
Max waterlift	mmH2O	3.200 - 2.000
Max air flow	m3/h	450 - 150
Suction inlet	mm	50
Construction		AISI304 stainless steel
Noise level (EN ISO 3744)	dB(A)	70 - 73

Filtering Unit

Primary filter		Star
Surface - Diameter	cm ² -mm	8.000 - 280
Material - Efficiency	IEC 60335-2-69	Poliestere ANT M
Cleaning system		Manual

Collection unit

Capacity	lt	25
Collection system		Tilting container

Encumbrances

Dimensions	cm	77 x 45 x 60h
Weight	kg	35 - 58

APPLICATIONS: Glass  Food, chemical and pharmaceutical industry

 **DUPUY**

All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

Fixed suction units

INDUSTRIAL VACUUM CLEANERS

SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

FILTERING UNIT

The antistatic polyester stellar filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

OPTIONALS

- Earthing