

# Silovac 100T Thre-phase vacuuming silos

INDUSTRIAL VACUUM CLEANERS



- ✓ Vacuuming silos designed for vacuuming large quantities of materials and direct discharge into big-bags or collection drums.
- ✓ Material discharge system with butterfly valve.
- ✓ Easy and quick big-bag bagging.
- ✓ Large surface filter for fine dust with integrated manual cleaning system.
- ✓ Large capacity detachable container. Forklift intakes.

## Suction unit

Voltage	V - Hz	400 - 50 3~
Power	kW	3
Max waterlift	mmH2O	2.600
Max air flow	m3/h	370
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	72

## Filtering Unit

Primary filter		Star
Surface - Diameter	cm <sup>2</sup> -mm	20.000 - 420
Material - Efficiency	IEC 60335-2-69	Polyester L
Cleaning system		Manual

## Collection unit

Capacity	lt	100
Collection system		Big-Bag
Discharge system		Butterfly valve

## Encumbrances

Dimensions	cm	139x126x315h
Weight	kg	170

APPLICATIONS: Mechanical industry Glass  Food, chemical and pharmaceutical industry Wood and plastic



All data mentioned in this document may change without notice.  
Tutti i dati in questo documento potrebbero variare senza preavviso.

[www.dupuyvacuums.com](http://www.dupuyvacuums.com)  
[info@dupuy.it](mailto:info@dupuy.it)

# Silovac 100T Thre-phase vacuuming silos

INDUSTRIAL VACUUM CLEANERS

## **SUCTION UNIT**

---

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

## **FILTERING UNIT**

---

The filter can be cleaned by means of the integrated mechanical cleaning system: an external filter shaking lever shakes the filter with a vertical movement, ensuring an effective and safe cleaning action, maintaining constant suction power and preventing the dispersion of dust into the environment.

## **COLLECTION UNIT**

---

The material is unloaded directly into big-bags.