

SKY 250 – 500 Oil mist extractors

AIR FILTRATION SOLUTIONS



- ✓ Reduced energy consumption
- ✓ Quick and easy maintenance.
- ✓ Easy installation on the machine.
- ✓ Quick and easy filter replacement system.

Suction unit

Voltage	V - Hz	400 - 50 ~ 3
Power	kW	0,12 - 0,18
Max air flow	m3/h	250 - 500
Suction inlet	mm	100
Construction		Painted steel
Noise level (EN ISO 3744)	dB(A)	62

Filtering Unit

Primary filter		Cartridge
Surface - Diameter	cm ² -mm	2.300/20.000 - 280
Cleaning system		Manual
Primary filter		Multilayer or Cartridge

Collection unit

Cyclon unit		Integrated
-------------	--	------------

Encumbrances

Dimensions	cm	Ø39 x 47h
Weight	kg	17 - 18

APPLICATIONS: Mechanical industry



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

SKY 250 – 500 Oil mist extractors

AIR FILTRATION SOLUTIONS

SUCTION UNIT

The suction unit is a low-power, low-consumption, high airflow blower.

FILTERING UNIT

Versatility of filtration: multi-layer filter (standard) or pleated cartridge with a high filtration surface area and a coalescing pre-filter

COLLECTION UNIT

Vacuumed and filtered oils and emulsions settle on the wall of the vacuum cleaner and can be recovered through the discharge hose.

OPTIONALS

- ✔ Kit for air outlet fan
- ✔ Installation kit with riser
- ✔ Installation kit with adjustable riser
- ✔ Wall mounting kit.
- ✔ Adjustable column for floor fixing from 1.5 to 2.5 m.
- ✔ Cyclone pre-filter kit.