



- ✓ Extremely silent.
- ✓ Release container with the possibility of using disposable bags.
- ✓ Simultaneous vacuuming of dust, liquids and solids.
- ✓ Large surface filter for fine dust with integrated manual cleaning system.
- ✓ Maintenance-free motor suitable for continuous operation.

#### Suction unit

Voltage	V - Hz	400 - 50 3~
Power	kW	7,5
Max waterlift	mmH2O	4.000
Continuous water lift	mmH2O	2.700
Max air flow	m3/h	700
Relief valve		Integrated
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	77

#### Filtering Unit

Primary filter		Star
Surface - Diameter	cm <sup>2</sup> -mm	35.000 - 420
Material - Efficiency	IEC 60335-2-69	Polyester L
Cleaning system		Manual

#### Collection unit

Capacity	lt	100
Collection system		Release container

#### Encumbrances

Dimensions	cm	119x65x180h
Weight	kg	182

APPLICATIONS: Glass Mechanical industry



General housekeeping



Food, chemical and pharmaceutical industry

### **SUCTION UNIT**

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

### **FILTERING UNIT**

The antistatic polyester pocket filter is located inside the steel filtering chamber and protects the suction unit, ensuring high dust retention and purity of the exhaust air thanks to its large surface area and high filtration efficiency. A manual cleaning system, consisting of a vertically moving filter shaker, allows the operator to clean the filter effortlessly at any time, extending the filter's life and preventing it from becoming saturated and reducing suction power. The suction system positioned below the filter allows the simultaneous suction of dust, solids and liquids without the need to replace or remove the filter.

### **COLLECTION UNIT**

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

### **OPTIONALS**

- ✓ Nomex filter - heat resistant up to 250°
- ✓ Hepa absolute filter /h14
- ✓ Large surface filter cat. m ptfе
- ✓ Stainless steel chamber
- ✓ Earthing
- ✓ Cyclone for filter protection
- ✓ Additional silencer
- ✓ Forklift intakes