

CVAC Fixed suction unit for vacuuming systems

CENTRAL VACUUM SYSTEMS – CENTRAL VACUUM UNITS AND FILTER SILOS



Suction unit

Voltage	V - Hz	400 - 50 ~ 3
Power	kW	4 - 7,5
Max waterlift	mmH2O	3.200 - 3.600
Continuous water lift	mmH2O	2.600 - 3.000
Max air flow	m3/h	420 - 700
Relief valve		Integrated
Suction inlet	mm	60 - 70
Construction		Painted steel
Noise level (EN ISO 3744)	dB(A)	74 - 77

Filtering Unit

Cleaning system	Manual
-----------------	--------

Collection unit

Encumbrances

Dimensions	cm	67 x 63 x 131h
------------	----	----------------

APPLICATIONS: Cementitious



Food, chemical and pharmaceutical industry

Glass

Steel mills and foundries

Sandblasting



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

CVAC Fixed suction unit for vacuuming systems

CENTRAL VACUUM SYSTEMS – CENTRAL VACUUM UNITS AND FILTER SILOS

SUCTION UNIT

It is supplied complete with electrical panel for starting up the suction unit and with sequencer board for managing cartridge cleaning cycles.

A pressure relief valve protects the motor from overheating, ensuring the supply of air for cooling.

OPTIONALS

- ✓ Additional silencer
- ✓ Inverter