

Oilvac 200

INDUSTRIAL VACUUM CLEANERS



- ✓ Save money by recovering and reusing cutting oil and emulsion.
- ✓ Large grid basket to collect metal chips and oil microfiltration filters to remove dust and metal particles.
- ✓ Liquid level monitored by a floating device to stop when the container is full.

Suction unit

Voltage	V - Hz	230 - 50 1~
Power	kW	3 x 1,1 - 2 x 1,6
Max waterlift	mmH2O	2.400
Max air flow	m3/h	540
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	78

Filtering Unit

Primary filter		Star
Surface - Diameter	cm ² -mm	14.000 - 420
Material - Efficiency	IEC 60335-2-69	M ANT Water-oil repellent

Collection unit

Powder capacity	lt	30
Liquid capacity	lt	200
Floating device		Electric
Discharge system		Submersible pump

Encumbrances

Dimensions	cm	122x62x130h
Weight	kg	205

APPLICATIONS: Mechanical industry



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

Oilvac 200

INDUSTRIAL VACUUM CLEANERS

SUCTION UNIT

Suction is generated by three carbon brush by-pass motors activated by independent switches located on a solid metal head, soundproofed with sound-absorbing material.

FILTERING UNIT

A float stops the suction when the liquid in the container reaches the maximum level, preventing spillage.

The polyester star filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The vacuum cleaner is mounted on a sturdy metal frame and fitted with heavy-duty industrial wheels for easy manoeuvrability also on uneven surfaces.

OPTIONALS

- ✓ Ppl oil filtration kit up to 100 microns (suction)