







- Ø Accessories included, ideal for cleaning professionals.
- Ompact and portable industrial vacuum cleaner.
- A powerful by-pass motor with independent cooling

| Suction unit | | |
|-----------------------|----------------|-------------|
| Voltage | V - Hz | 230 - 50 1~ |
| Power | kW | 1,1 |
| Max waterlift | mmH2O | 2.400 |
| Max air flow | m3/h | 180 |
| Filtering Unit | | |
| Primary filter | | Bag |
| Surface - Diameter | cm²-mm | 2.000 - 400 |
| Material - Efficiency | IEC 60335-2-69 | Polyester L |
| Cleaning system | | Manual |
| Collection unit | | |
| Capacity | lt | 65 |
| Floating device | | Mechanical |
| Encumbrances | | |
| Dimensions | cm | 68x53x89h |
| Weight | kg | 21 |
| | | |

APPLICATIONS:



General housekeeping



SUCTION UNIT

Suction is generated by one carbon brush by-pass motor activated by independent switches located on a solid metal head that protects the motor from possible blows and ingress of external bodies, keeping the noise level to a minimum.

FILTERING UNIT

The polyester bag filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The vacuumed material is collected in a stainless steel detachable container, mounted on wheels, which allows for quick and clean disposal. Bagging is also possible.

