









- Possibility of turning upside down from 50° to 90° with the help of a forklift truck. Simple and effective DU-PUY patent system.
- Large capacity tilting vacuum cleaner for solids and liquids. Designed to make simplify the vacuuming of large quantities of different materials.

Suction unit		
Voltage	V - Hz	230 - 50 1~
Power	kW	3,3
Max waterlift	mmH2O	2.400 - 3.600
Max air flow	m3/h	540 - 340
Suction inlet	mm	90
Noise level (EN ISO 3744)	dB(A)	77-78
Filtering Unit		
Primary filter		Star
Surface - Diameter	cm²-mm	14.000 - 420
Material - Efficiency	IEC 60335-2-69	Polyester L
Cleaning system		Manual
Collection unit		
Capacity	lt	200
Discharge system		Tilting container
Encumbrances		
Dimensions	cm	109x94x135h - 109x94x136h
Weight	kg	155 - 157

APPLICATIONS: Mechanical industry Glass



SUCTION UNIT

Suction is generated by three carbon brush by-pass motors activated by independent switches located on a solid metal head, soundproofed with sound-absorbing material.

FILTERING UNIT

The polyester star filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The vacuumed material is collected in the front discharge bucket, allowing the material to be disposed of quickly and without contamination. The vacuum cleaner is mounted on a sturdy powder coated steel frame, fitted with polyurethane wheels and designed for forklift intakes.

The container is compact and contains a sieve grid to separate the solids.

OPTIONALS

- Ø Oil-proof seal
- ✓ Nomex filter heat resistant up to 250°
- Antistatic filter class m
- Hydro-oleophobic filter class m
- Ø Oil-chip separation grid

