W2 single phase industrial vacuum cleaner

INDUSTRIAL VACUUM CLEANERS









- Accessories included, ideal for cleaning professionals.
- 100% steel construction.
- Simultaneous vacuuming of dust, liquids and solids.

Suction unit		
Voltage	V - Hz	230 - 50 1~
Power	kW	2 x 1,1
Max waterlift	mmH2O	2.400
Max air flow	m3/h	360
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	78
Filtering Unit		
Primary filter		Star
Surface - Diameter	cm²-mm	20.000 - 420
Cleaning system		Manual
Collection unit		
Capacity	lt	40
Collection system		Release container
Encumbrances		
Dimensions	cm	63x57x116h
Weight	kg	44

APPLICATIONS: Mechanical industry

Wood and plastic



General housekeeping



Food, chemical and pharmaceutical industry



W2 single phase industrial vacuum cleaner

INDUSTRIAL VACUUM CLEANERS

SUCTION UNIT

Suction is generated by two carbon brush by-pass motors activated by independent switches located on a solid metal head, soundproofed with sound-absorbing material.

FILTERING UNIT

The antistatic polyester stellar filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

The filter can be cleaned by means of the integrated mechanical cleaning system: an external filter shaking lever shakes the filter with a vertical movement, ensuring an effective and safe cleaning action, maintaining constant suction power and preventing the dispersion of dust into the environment.

COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

OPTIONALS

- Nomex filter heat resistant up to 250°
- Hepa absolute filter /h14
- Accessory basket
- Ptfe-treated filter class m
- Antistatic filter class l
- Antistatic filter class m
- Stainless steel container and filter chamber
- Stainless steel container
- Earthing
- Local remote start-up

