

WD 3000 1/2D – ATEX-certified vacuum cleaner for dusts and liquids in areas with a high risk of explosion

INDUSTRIAL VACUUM CLEANERS



- ✓ The inside of the filter chamber is ATEX Z20 certified; the outside of the machine is Z21 certified
- ✓ AISI304 stainless steel container
- ✓ Tilting container for easy emptying.

Suction unit

Voltage	V - Hz	230 - 50 1~
EX category		CE EX 21 1/2D
Max air flow	m3/h	215
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	74

Filtering Unit

Primary filter		Bag
Surface - Diameter	cm ² -mm	5.000-420
Cleaning system		Manual
Filtration efficiency		M ANT
Primary filter		Standard
Surface - Diameter	cm ² -mm	11.000

Collection unit

Capacity	lt	60
Collection tank		AISI304 stainless steel
Collection system		Release container

Encumbrances

Dimensions	cm	62x60x115h
Weight	kg	38

APPLICATIONS:



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

WD 3000 1/2D – ATEX-certified vacuum cleaner for dusts and liquids in areas with a high risk of explosion

INDUSTRIAL VACUUM CLEANERS

SUCTION UNIT

The suction unit is equipped with a brushless motor which, thanks to the absence of carbon brushes, allows the machine to be used in the safest conditions, even in potentially explosive atmospheres. The motor is protected by a series of efficient filters and is activated by an independent switch located on a solid metal head, soundproofed with sound-absorbing material. The head is supplied as standard with a vacuum gauge and voltage presence indicators.

FILTERING UNIT

The polyester bag filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The vacuumed material is collected in a stainless steel container, mounted on wheels, which allows for quick and clean disposal.