

WD 3000 EX 1/3D

INDUSTRIAL VACUUM CLEANERS



- ✓ The inside of the filter chamber is ATEX Z20 certified; the outside of the machine is Z22 certified

APPLICATIONS:



Suction unit

Voltage	V - Hz	230 - 50 1~
Marking	II 1/3D Ex h tb IIIC T80° (int) /T95°C (ext) Da/Dc	
Usage area	Hazardous location	
EX category	CE EX 22 1/3D	
Power	kW	1 x 1,1 by-pass
Max waterlift	mmH2O	2.400
Max air flow	m3/h	180
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	76

Filtering Unit

Primary filter	Bag	
Surface - Diameter	cm ² -mm	5.000-420
Total filtering surface area	cm ²	11.000
Cleaning system	Manual	
Filtration efficiency	M ANT	
Primary filter	Standard	
Surface - Diameter	cm ² -mm	11.000
Filter class		

Collection unit

Capacity	lt	60
Collection system	Release container	

Encumbrances

Dimensions	cm	62x60x115h
Weight	kg	38

WD 3000 EX 1/3D

INDUSTRIAL VACUUM CLEANERS

SUCTION UNIT

Suction is generated by one carbon brush by-pass motor activated by independent switches located on a solid metal head, soundproofed with sound-absorbing material.

FILTERING UNIT

The polyester bag filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The vacuumed material is collected in a stainless steel container, mounted on wheels, which allows for quick and clean disposal.