

# W2 ACD – ACD industrial vacuum cleaner for non-continuous applications in non-ATEX zones

INDUSTRIAL VACUUM CLEANERS



- ✓ ACD classification for vacuuming combustible dust in non-classified zones

## Suction unit

Voltage	V - Hz	230 - 50/60 1~
Usage area		Ordinary location
EX category		CE ACD
Power	kW	2 x 1,1 bypass
Max waterlift	mmH2O	2.460
Max air flow	m3/h	360
Noise level (EN ISO 3744)	dB(A)	76

## Filtering Unit

Primary filter		Star
Surface - Diameter	cm <sup>2</sup> -mm	20.000 - 420
Cleaning system		Manual
Filtration efficiency		M ANT
Primary filter		Standard
Filter class		

## Collection unit

Capacity	lt	40
Collection tank		Painted

## Encumbrances

Dimensions	cm	63x57x116h
Weight	kg	10

## APPLICATIONS:

# W2 ACD – ACD industrial vacuum cleaner for non-continuous applications in non-ATEX zones

INDUSTRIAL VACUUM CLEANERS

## **SUCTION UNIT**

---

## **FILTERING UNIT**

---

Inside the steel filter chamber is the antistatic polyester pocket filter, which protects the suction unit and prevents the risk of sparks due to static energy build-up. An absolute filter (99.995% of 0.18 micron, Class H) is included to ensure the retention of the finest dust and the purity of the exhaust air.

## **COLLECTION UNIT**

---

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.