

# M70 PN

## INDUSTRIAL VACUUM CLEANERS



✓ Extremely silent.

### Suction unit

Voltage	V - Hz	400 - 500 3~
Power	kW	5,5
Max waterlift	mmH2O	3.600
Continuous water lift	mmH2O	3.000
Max air flow	m3/h	530
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	74

### Filtering Unit

Primary filter		Cartridge
Surface - Diameter	cm <sup>2</sup> -mm	80.000 - 420
Material - Efficiency	IEC 60335-2-69	Poliestere ANT M
Cleaning system		Automatico PN

### Collection unit

Capacity	lt	100
----------	----	-----

### Encumbrances

Dimensions	cm	119x65x200h
Weight	kg	149

APPLICATIONS: Mechanical industry

Glass



General housekeeping



Food, chemical and pharmaceutical industry



All data mentioned in this document may change without notice.  
Tutti i dati in questo documento potrebbero variare senza preavviso.

[www.dupuyvacuums.com](http://www.dupuyvacuums.com)  
[info@dupuy.it](mailto:info@dupuy.it)

### **SUCTION UNIT**

---

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

### **FILTERING UNIT**

---

The polyester pocket filter is located inside the steel filtering chamber and protects the suction unit, ensuring high dust retention and purity of the exhaust air thanks to its large surface area and high filtration efficiency. A manual cleaning system, consisting of a vertically moving filter shaker, allows the operator to clean the filter effortlessly at any time, extending the filter's life and preventing it from becoming saturated and reducing suction power. The suction system positioned below the filter allows the simultaneous suction of dust, solids and liquids without the need to replace or remove the filter.

### **COLLECTION UNIT**

---

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

### **OPTIONALS**

---

- ✔ Nomex filter - heat resistant up to 250°
- ✔ Hepa absolute filter /h14
- ✔ Large surface filter cat. m ptfе
- ✔ Stainless steel container
- ✔ Earthing
- ✔ Cyclone for filter protection
- ✔ Pressure relief valve
- ✔ Additional silencer
- ✔ Forklift intakes