

# Oilvac 200 T

## INDUSTRIAL VACUUM CLEANERS



- ✓ Save money by recovering and reusing cutting oil and emulsion.
- ✓ Large grid basket to collect metal chips and oil microfiltration filters to remove dust and metal particles.
- ✓ Liquid level monitored by a floating device to stop when the container is full.

### Suction unit

Voltage	V - Hz	400 - 50 3~
Power	kW	3
Max waterlift	mmH2O	3.200
Max air flow	m3/h	350
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	76

### Filtering Unit

Primary filter		Star
Surface - Diameter	cm <sup>2</sup> -mm	14.000
Material - Efficiency	IEC 60335-2-69	M ANT Water-oil repellent

### Collection unit

Powder capacity	lt	30
Liquid capacity	lt	200
Floating device		Electric
Discharge system		Submersible pump

### Encumbrances

Dimensions	cm	122x62x155h
Weight	kg	224

**APPLICATIONS:** Mechanical industry



All data mentioned in this document may change without notice.  
Tutti i dati in questo documento potrebbero variare senza preavviso.

[www.dupuyvacuums.com](http://www.dupuyvacuums.com)  
[info@dupuy.it](mailto:info@dupuy.it)

# Oilvac 200 T

INDUSTRIAL VACUUM CLEANERS

## SUCTION UNIT

Three-phase model with 3kW side channel.

## FILTERING UNIT

A float stops the suction when the liquid in the container reaches the maximum level, preventing spillage.

The polyester star filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

## COLLECTION UNIT

The vacuum cleaner is mounted on a sturdy metal frame and fitted with heavy-duty industrial wheels for easy manoeuvrability also on uneven surfaces.

A grid basket inside the container separates solids (chips, metal swarf) from liquids, which drain to the bottom of the container. The liquid is quickly disposed of via a manual liquid drain valve.

## OPTIONALS

✓ Recommended accessory Ø50