

M70-90 ACD

INDUSTRIAL VACUUM CLEANERS



- ✓ ACD classification for vacuuming combustible dust in non-classified zones

Suction unit

Voltage	V - Hz	400 - 50 3~
Power	kW	5,5 - 7,5
Max waterlift	mmH2O	3.000 - 2.700
Max air flow	m3/h	530 - 700
Electrical protection	IP	65
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	74 - 77

Filtering Unit

Primary filter		Star
Surface - Diameter	cm ² -mm	35.000 - 420
Total filtering surface area	cm ²	26.000 - 52.000
Material - Efficiency	IEC 60335-2-69	M ANT

Collection unit

Capacity	lt	100
----------	----	-----

Encumbrances

Dimensions	cm	119x65x180h
Weight	kg	150 - 183

APPLICATIONS: Sandblasting



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

M70-90 ACD

INDUSTRIAL VACUUM CLEANERS

FILTERING UNIT

The filter can be cleaned by means of the integrated mechanical cleaning system: an external filter shaking lever shakes the filter with a vertical movement, ensuring an effective and safe cleaning action, maintaining constant suction power and preventing the dispersion of dust into the environment.

COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

OPTIONALS

- Star-delta starter panel board